

## 2019-2020 OHSAA Vault Chart

GROUP I HANDSPRINGS, YAMASHITAS	GROUP II HANDSPRINGS with or without 1/1 TURN - SALTO FORWARD OR BACKWAR	GROUP III TSUKAHARA or ½ on - SALTO FWD OR BWD with or without TURN	GROUP IV Round - off, Flic-flac on - SALTO FWD OR BWD with or without LA TURN	GROUP V Round - off, Flic-flac with ½ or 1/1 turn on - HNDSPG or SALTO FWD OR BWD with or without LA TURN
1.101 Handspring 8.6 1.102 Hndspring- ½ 8.7 1.103 Yamashita 8.6 1.104 Yami - ½ 8.7 1.105 ½ on -½ off 8.7 OR ¼ on - ¾ off 1.106 ¼ - ½ on - Repulsionoff 7.7 1.107 ¼ twist on - 8.5 ¼ twist off - to land facing away from table**		<p style="text-align: center;"><i>Note for the J.O. Program:</i> All Group 3 vaults may be performed with a 90° to 180° LA turn in the first flight</p>		<p style="text-align: center;">All Group 5 vaults described as a flic- flac with a 1/1 (360°) turn on may be performed with a ¾ (270°) to 1/1 (360°) LA turn in the first flight</p>
1.201 Hsp - 1/1 9.0 1.202 Hsp - 1½ 9.4 1.203 Yami - 1/1 9.0 1.205 ½ on - 1½ off 9.3 or ¼ on - 1¾ off 1.206 ½ on - 1/1 off 8.9 or ¼ on - 1¼ off 1.207 1/1 on - H/Y 9.0 1.208 1/1 on - ½ off 9.3		3.201 Tsukahara Tuck 9.6	4.101 RO, FF on - Repulsion off 8.0 4.102 RO, FF on - Repulsion ½ off 8.7 4.201 RO, FF on - 1/1 twist off 9.1 4.202 RO, FF on - 1½ twist off 9.3 (Allen)  4.203 RO, FF on - Back Tuck 9.6	5.101 RO, FF ½ on - Hndsprg off 8.9    5.201 RO, FF ½ on - 1/1 twist off 9.2 5.202 RO, FF ½ on - 1½ twist off 9.4 5.207 RO, FF 1/1 on - 1/1 twist off 9.3
1.301 Hsp - 2/1 9.9 1.306 ½ on - 2/1 off 9.8 or ¼ on - 2¼ off 1.307 1/1 on - 1/1 off 9.7	2.301 Hsp - Front Tuck 10.0 2.302 Hsp - Front Tuck ½ 10.0 2.304 Hsp - Front Pike 10.0 2.310 Fr. Hndsp onto board, Hsp. - Fr. Tuck (llg) 10.0 2.311 Fr. Hndsp onto board, Hsp. - Fr. Pike (Garbarino) 10.0	3.302 Tsuk Tuck 1/1 10.0 3.303 Tsuk Pike 9.7 3.304 Tsuk layout 10.0 3.306 ½ on - ½ off, Fr. Tuck 10.0 or ¼ on - ¾ off, Fr. Tuck (land facing out) or Tsuk tuck ½ 3.308 ½ on - ½ off, Fr. Tuck ½ 10.0 (Shible) or ¼ on - ¾ off, Fr. Tuck ½  3.305 Front handspring on board, ¼- ½ on, back salto pike 9.8	4.301 RO, FF on - 2/1 twist off 9.8 (Allen) 4.303 RO, FF on - B. Tuck 1/1 10.0 4.304 RO, FF on - B. Pike 9.7 4.305 RO, FF on - B. Layout 10.0 4.306 RO, FF on - B. Layout 1/1 10.0 4.307 RO, FF on - ½ off, Fr. Tuck 10.0 or RO, FF on - B. Tuck ½	5.301 RO, FF ½ on - Front Tuck 10.0 5.312 RO, FF ½ on - 2/1 twist off 9.9
			4.407 RO, FF on - ½ turn off, Fr. Tuck ½ (Beckman) 10.0	Revised 10/19